



GREENBOX™
THERMAL MANAGEMENT SYSTEM

PRODUCT OFFERING

e¹⁸ e⁴² e²⁴

ENTROPY
PHASE CHANGE
TECHNOLOGY

-20°C to +50°C

120+ HOURS



1-877-4GRNBOX
GREENBOXSYSTEMS.COM

GREENBOX 9



Product Code	Description	External Dimensions	Payload Dimensions	Weight
09VPRFU1	24 Hour (-24 to -18C) 4 E Packs	9 x 9 x 9	7.1 x 7.5 x 3.6	7.9 lbs.
09VPRFU2	48 Hour (-24 to -18C) 6 E Packs	9 x 9 x 9	7.1 x 7.5 x 1.6	10.6 lbs.
09VPRRU2	48 Hour (2 to 8C) 4 E Packs	9 x 9 x 9	7.1 x 7.5 x 3.6	7.9 lbs.
09VPRRU3	72 Hour (2 to 8C) 6 E Packs	9 x 9 x 9	7.1 x 7.5 x 1.6	10.6 lbs.
09VPRCU2	48 Hour (20 to 25C) 4 E Packs	9 x 9 x 9	7.1 x 7.5 x 3.6	7.9 lbs.
09VPRCU3	72 Hour (20 to 25C) 6 E Packs	9 x 9 x 9	7.1 x 7.5 x 1.6	10.6 lbs.

GREENBOX 12



12VPRFU3	72 Hour (-24 to -18C) 8 E Packs	12 x 12 x 12	9.2 x 9.5 x 1.6	28.0 lbs.
12VPRRU3	72 Hour (2 to 8C) 4 E Packs	12 x 12 x 12	9.6 x 9.6 x 5.5	17.0 lbs.
12VPRRU4	96 Hour (2 to 8C) 6 E Packs	12 x 12 x 12	9.2 x 9.6 x 3.6	22.5 lbs.
12VPRRU5	120 Hour (2 to 8C) 8 E Packs	12 x 12 x 12	9.2 x 9.5 x 1.6	28.0 lbs.
12VPRCU3	72 Hour (20 to 25C) 4 E Packs	12 x 12 x 12	9.6 x 9.6 x 5.5	17.0 lbs.
12VPRCU4	96 Hour (20 to 25C) 6 E Packs	12 x 12 x 12	9.2 x 9.6 x 3.6	22.5 lbs.

GREENBOX 24



24VPRFU3	72 Hour (-24 to -18C) 12 E Packs	24 x 14 x 12	17.5 x 7.6 x 9.3	45.8 lbs.
24VPRRU5	120 Hour (2 to 8C) 12 E Packs	24 x 14 x 12	17.5 x 7.6 x 9.3	45.8 lbs.
24VPRCU7	168 Hour (20 to 25) 12 E Packs	24 x 14 x 12	17.5 x 7.6 x 9.3	45.8 lbs.

INFLATER 9 & 12



231FP205	24 Hour (20 to 25C) 2 Pillow Panels	9 x 11	Varies	1.0 lb.
244FP026	24 Hour (2 to 8C) 2 Pillow Panels	12 x 14	Varies	1.9 lbs.
244FP205	24 Hour (20 to 25C) 2 Pillow Panels	12 x 14	Varies	1.9 lbs.

ThermoSafe Brands
(SBU Headquarters)
3930 North Ventura Drive
Arlington Heights, Illinois
60004 USA
Tel +1 800 505 1886
Fax +1 847 398 0653

ThermoSafe Brands Europe Ltd
Quartermown Industrial Estate
Mallow, Co. Cork
Ireland
Tel +353 22 55112
Fax +353 22 55114

ThermoSafe Brands Asia Pte Ltd
18, Boon Lay Way
#07-133/134/135, TradeHub 21
Singapore 609966
Singapore
Tel +65 6323 3390
Fax +65 6323 3360

ThermoSafe®
Temperature Assurance Solutions